



- 开启角度: 95度
- 铰杯厚度: 12毫米
- 铰杯直径: 26毫米
- 面板(K)尺寸: 3毫米-5毫米
- 材质: 铁镀锌
- 门可选用板厚: 14毫米-22毫米
- Opening angle: 95°
- Depth of hinge cup: 12mm
- Diameter of hinge cup: 26mm
- Drilling distance on the door(K): 3-5mm
- Material: cold rolled steel, nickel plated
- Range of door thickness: 14-22mm


**R206系列(普通型)自关铰链功能图 R206 Installation dimensions**

D: 盖位计算值表 Overlay  
A: 间隙位计算值表 Gap



**R206A** 全盖 Full overlay

$$H = 10 + K - D$$




$\begin{matrix} H & K \\ D \end{matrix}$	3	4	5
0	13	14	15
2	11	12	13
4	9	11	11



**R206B** 半盖 Half overlay

$$H = 1.5 + K - D$$




$\begin{matrix} H & K \\ D \end{matrix}$	3	4	5
0	4.5	5.5	6.5
2	2.5	3.5	4.5
4	0.5	1.5	2.5




**R206C** 内嵌 Insert

$$H = -0.5 + K + A$$



$\begin{matrix} H & K \\ A \end{matrix}$	3	4	5
0	-2.5	-3.5	-4.5
2	-0.5	-1.5	-2.5
4	1.5	0.5	-0.5

**铰杯种类 Hinge cup types**



**可配底座 Plate**

序号 No	名称 Item no.	H值 H Value	孔型/安装尺寸L Hole type/Mounting dimension L	类型 type
1	I9B	H=0	两孔 two holes/25mm	普通 Normal
2	I8	H=0	四孔 four holes/37mm	普通 Normal
3				

安装尺寸L(Mounting dimension L)

安装尺寸L(Mounting dimension L)

侧板边沿 Side board edge

侧板边沿 Side board edge

