

H40

Ø40mm SOFT-CLOSING INDIVISIBLE HINGE
40 杯缓冲固装铰链



- 开启角度: 95度
- 铰杯厚度: 13毫米
- 铰杯直径: 40毫米
- 面板(K)尺寸: 3毫米-10毫米
- 材质: 铁镀镍
- 门可选用板厚: 20毫米-30毫米
- Opening angle: 95°
- Depth of hinge cup: 13mm
- Diameter of hinge cup: 40mm
- Drilling distance on the door(K): 3-10mm
- Material: cold rolled steel, nickel plated
- Range of door thickness: 20-30mm


H40系列内置阻尼自动铰链功能图 H40 Installation dimensions

D: 盖位计算值表 Overlay
A: 间隙位计算值表 Gap



H40A 全盖 Full overlay

$$H=19+K-D$$




$\begin{matrix} K \\ H \end{matrix}$	3	4	5	6	7
D					
0	22	23	24	25	26
2	20	21	22	23	24
4	18	19	20	21	22



H40B 半盖 Half overlay

$$H=10+K-D$$




$\begin{matrix} K \\ H \end{matrix}$	3	4	5	6	7
D					
0	13	14	15	16	17
2	11	12	13	14	15
4	9	10	11	12	13




H40C 内嵌 Insert

$$H=1+K+A$$



$\begin{matrix} K \\ H \end{matrix}$	3	4	5	6	7
A					
0	-4	-5	-6	-7	-8
2	-2	-3	-4	-5	-6
4	0	-1	-2	-3	-4


铰杯种类 Hinge cup types



可配底座 Plate

序号 No	名称 Item no.	H值 H Value	孔型/安装尺寸L Hole type/Mounting dimension L	类型 type
1	F10S	H=0	两孔 two holes/37mm	普通 Normal
2	F40T/ F40S	H=0	四孔 four holes/37mm	普通 Normal
3				

安装尺寸L(Mounting dimension L)



安装尺寸L(Mounting dimension L)

